

TELECONTROL T10D / T10D-GSM



room thermostat

- LCD displaying the room temperature
- turning on and off the heating
- adjusting the room temperature
- anti-freeze temperature function
- selectable standard heating mode, cooling mode and underfloor heating mode

control via phone or cell phone

- voice communication in English language
- turning on and off the heating
- measuring the room temperature
- adjusting the room temperature
- measuring external temperature (with optional external temperature sensor)
- changing the user settings



Room thermostat with built-in voice communication interface for remote control via phone or cell phone.

Highly integrated, built-in communication interface enables the user, not only to turn on and off the heating from the distance, but also to access all functions of room thermostat from the distance. Thus the user can measure the room temperature, adjust the room temperature, measure the external temperature...

While in object, all the functions of classic room thermostat are available: LCD displaying the room temperature, direct adjustment of the temperature, turning on and off the heating....



other characteristics

- blue LCD backlight
- uses analog telephone line or ISDN line with analog output
- output status light indicator
- user changeable password
- there is no interference with the operation of other devices connected to the same telephone line


optional equipment

- external temperature sensors KTS4 and KTS5

APPLICATION EXAMPLES


1. Application: Central heating regulation - connecting to dedicated room thermostat input

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM




2. Application: central heating regulation - connecting to water circulation pump

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM




3. Application: Electric heating system regulation (power < 3kW)

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM




4. Application: Electric heating system regulation (power > 3kW)

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM




5. Application: Electric underfloor heating system $P > 3\text{kW}$ with floor temperature limiting

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM




6. Application: Air-conditioner with autorestart function

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM



7. Application: Computer server room temperature supervision and excess temperature notification by phone. Remote phone control of backup cooling device.

TELECONTROL
T10D
T10D-GSM
T10DP
T10DP-GSM



8. Application: Central heating control, air-conditioner control, garage door control, burglary notification, carbon monoxide notification, fire notification, refrigerator/freezer temperature supervision and error (melting) notification.

TELECONTROL
T20DP
T20DP-GSM

